

# Thermo Scientific Orion Star A326

Premium pH/RDO/dissolved oxygen portable meter

The Thermo Scientific™ Orion™ Star A326 pH/RDO/Dissolved Oxygen Portable Meter is the top choice for testing samples anywhere. It is rugged and dependable, making it ideal for every sample, every day, everywhere.



The Thermo Scientific Orion Star A326 pH/RDO/Dissolved Oxygen Portable Meter is the top choice for advanced measurements on location. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display shows one or both pH and DO channels with temperature. Additional helpful information includes electrode status, time, date, sample ID, user ID and calibration points.

## Features and Benefits

- Easy meter operation assured with on-screen text prompts, menu-specific function keys and a multi-language interface
- Don't miss a reading—AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals
- Up to 5 point pH calibration with automatic recognition for USA/NIST and DIN buffers or manual option for custom buffer values


- Easily get accurate DO results with automatic temperature, manual salinity and automatic/manual barometric pressure correction
- Calibrate DO using water-saturated air, air-saturated water, custom value using a Winkler titration or zero point calibration
- Non-volatile memory holds up to 5000 data points with time and date stamp
- Easily transfer data with the USB and RS232 ports and complimentary Orion Star Com computer software
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately)
- Perfectly portable, IP67-rated waterproof and protected to take anywhere
- 3 year meter replacement warranty



**Thermo**  
SCIENTIFIC

# Thermo Scientific Orion Star A326 pH/RDO/Dissolved Oxygen Portable Meter

Specifications	
<b>pH</b>	<b>Range:</b> -2.000 to 20.000 <b>Resolution:</b> 0.1, 0.01, 0.001 <b>Relative Accuracy:</b> ±0.002 <b>Calibration Points:</b> Up to 5 <b>Calibration Editing:</b> Yes
<b>mV/RmV</b>	<b>Range:</b> ±2000.0 mV <b>Resolution:</b> 0.1 mV <b>Relative Accuracy:</b> ±0.2 mV or ±0.05 % of reading whichever is greater <b>E<sub>H</sub> ORP Mode:</b> Yes
<b>Dissolved Oxygen</b>	<b>Polarographic</b> <b>Range:</b> 0 to 600 % saturation; 0 to 90 mg/L <b>Resolution:</b> 0.1, 1 % sat.; 0.01, 0.1 mg/L <b>Relative Accuracy:</b> ±2 % sat. or ±2 % of reading, whichever is greater; ±0.2 mg/L or ±2 % of reading, whichever is greater <b>RDO</b> <b>Range:</b> 0 to 500 % saturation; 0 to 50 mg/L <b>Resolution:</b> 0.1, 1 % sat.; 0.01, 0.1 mg/L <b>Relative Accuracy:</b> ±2 % sat. ≤ 200 % sat., ±10 % sat. > 200 % sat.; ±0.1 mg/L up to 8 mg/L, ±0.2 mg/L from 8 to 20 mg/L, 10 % of reading from 20 to 50 mg/L <b>Barometric Pressure Correction:</b> 400 to 850 mmHg, automatic or manual <b>Manual Salinity Factor Correction:</b> 0 to 45 ppt <b>Calibration:</b> Water saturated air, air saturated water, manual (Winkler) and zero point
<b>Temperature</b>	<b>Range:</b> -5 to 105 °C, 23 to 221 °F (RDO/DO: 0 to 50 °C, 32 to 122 °F) <b>Resolution:</b> 0.1 °C, 0.1 °F <b>Relative Accuracy:</b> ±0.1 °C, ±0.1 °F <b>Offset Calibration:</b> 1 point
<b>Datalogging</b>	<b>Memory:</b> 5000 with time and date stamp <b>Log Function:</b> Manual, ready (includes AUTO-READ), timed
<b>Inputs</b>	<b>pH Electrode:</b> BNC, reference pin <b>ATC Probe:</b> 8-pin mini-DIN <b>DO Probe:</b> 9-pin mini-DIN
<b>Output</b>	RS232, USB
<b>Power</b>	<b>AC Adapter:</b> Optional—universal, 100-240 VAC <b>Battery Power:</b> Included—4 AAs <b>Battery Life:</b> 800 hrs

 **Thermo Fisher Scientific**  
 Water Analysis Instruments  
 Chelmsford, MA USA  
 Quality Management System  
 Registered to ISO 9001

Meter Ordering Information	
<b>Part No.</b>	<b>Description</b>
<b>STARA3260</b>	<b>Orion Star A326 pH/RDO/Dissolved Oxygen Portable Meter</b> - Four AA batteries (installed) - Printed quick start guide and literature CD - USB computer cable
<b>STARA3265</b>	<b>Orion Star A326 pH/RDO/Dissolved Oxygen Portable Meter Kit</b> - 8107UWMMMD Orion ROSS Ultra Triode gel-filled epoxy-body pH/ATC electrode, 3 m cable - 087010MD Orion RDO optical DO probe with 3 m cable, stainless steel guard, calibration sleeve and optical cap - Orion pH 4, 7, 10 buffer pouches, 10 each - 810001 Orion ROSS storage solution, 475 mL - Protective armor with electrode holders and storage sleeve - Hard-sided field case - Four AA batteries (installed) - Printed quick start guide and literature CD - USB computer cable

Accessories Ordering Information	
<b>Part No.</b>	<b>Description</b>
<b>STARA-CS</b>	Orion Star A series portable meter hard-sided field case
<b>STARA-AR</b>	Orion Star A series portable meter armor with pH electrode holder, conductivity and DO probe holder, stand and adjustable hand-strap
<b>STARA-ESPH</b>	Orion pH electrode holder for portable Star A series meter armor
<b>810017</b>	Orion pH electrode storage sleeve for pH electrode holder
<b>STARA-ESCD</b>	Orion conductivity and DO probe holder for portable Star A series meter armor
<b>8107UWMMMD</b>	Orion ROSS Ultra Triode, 3 m cable
<b>087020MD</b>	Orion RDO optical DO probe, 6 m cable
<b>087030MD</b>	Orion RDO optical DO probe, 10 m cable
<b>087050MD</b>	Orion RDO optical DO probe, 15 m cable
<b>087100MD</b>	Orion RDO optical DO probe, 30 m cable
<b>1010003</b>	Universal power adapter, 100-240 V, 50/60 Hz
<b>910410-WA</b>	Orion pH 4.01 buffer pouches, 10 pack
<b>910710</b>	Orion pH 7.00 buffer pouches, 10 pack
<b>911010</b>	Orion pH 10.01 buffer pouches, 10 pack
<b>083005MD</b>	Orion polarographic DO probe, 1.5 m cable

For more information, contact your local Thermo Scientific products dealer or call our customer and technical service experts at 1-800-225-1480 (for the US and Canada) or visit [www.thermoscientific.com/water](http://www.thermoscientific.com/water).



[thermoscientific.com/water](http://thermoscientific.com/water)

© 2013 Thermo Fisher Scientific Inc. All rights reserved. Certified System StandardsMark logo is a trademark of SAI Global. All other trademarks are the property of Thermo Fisher Scientific Inc. & its subsidiaries



## Water Analysis Instruments

**North America**  
 Toll Free: 1-800-225-1480  
 Tel: 1-978-232-6000  
[info.water@thermo.com](mailto:info.water@thermo.com)

**Netherlands**  
 Tel: (31) 020-4936270  
[info.water.uk@thermo.com](mailto:info.water.uk@thermo.com)

**India**  
 Tel: (91) 22-4157-8800  
[wai.asia@thermofisher.com](mailto:wai.asia@thermofisher.com)

**Japan**  
 Tel: (81) 045-453-9175  
[wai.asia@thermofisher.com](mailto:wai.asia@thermofisher.com)

**China**  
 Tel: (86) 21-68654588  
[wai.asia@thermofisher.com](mailto:wai.asia@thermofisher.com)

**Singapore**  
 Tel: (65) 6778-6876  
[wai.asia@thermofisher.com](mailto:wai.asia@thermofisher.com)

**Australia**  
 Tel: (613) 9757-4300  
 in Australia (1300) 735-295  
[InfoWaterAU@thermofisher.com](mailto:InfoWaterAU@thermofisher.com)

**Thermo**  
 SCIENTIFIC

Part of Thermo Fisher Scientific